

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 2 of 9

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261	Avoid breathing vapour.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.

Special labelling of certain mixtures

EUH066	Repeated exposure may cause skin dryness or cracking.
--------	---

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Mixture of organic solvents

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification according to Regulation (EC) No. 1272/2008 [CLP]			
141-78-6	Ethyl acetate			< 50 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
123-86-4	n-Butyl acetate			< 25 %
	204-658-1	607-025-00-1	01-2119485493-29	
	Flam. Liq. 3, STOT SE 3; H226 H336 EUH066			
9004-70-0	Nitrocellulose, containing a maximum of 12,6% nitrogen			< 25 %
	Flam. Sol. 1; H228			
67-63-0	Propan-2-ol			< 20 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

Remove contaminated soaked clothing immediately.
Take away from danger area and lay down affected person.

After inhalation

Move to fresh air in case of accidental inhalation of vapours.
In the event of symptoms refer for medical treatment.
Artificial respiration and/or oxygen may be necessary.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 3 of 9

After contact with skin

Wash off with soap and plenty of water.
Consult a doctor if skin irritation persists.

After contact with eyes

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Seek medical treatment by eye specialist.

After ingestion

Do not induce vomiting.
Rinse out mouth and give plenty of water to drink.
Never give anything by mouth to an unconscious person.
Summon a doctor immediately.
Induce vomiting only upon the advice of a physician.

4.2. Most important symptoms and effects, both acute and delayed

May cause drowsiness or dizziness.
Causes serious eye irritation.
Repeated exposure may cause skin dryness or cracking.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptoms.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, dry chemical, carbon dioxide (CO₂), water-spray.

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Fire may produce:
carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x)

5.3. Advice for firefighters

Use breathing apparatus with independent air supply.
Protective suit.

Additional information

Cool containers at risk with water spray jet.
Flashback at a long distance is possible.
The vapour/air mixture is explosive, even in empty, uncleaned receptacles.
Vapours are heavier than air and spread along ground.
Fire residues and contaminated firefighting water must be disposed of in accordance with the local regulations.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Keep away sources of ignition.
In case of vapour formation use respirator.
Ensure adequate ventilation.
Use personal protective clothing.
Avoid contact with skin, eyes and clothing.

6.2. Environmental precautions

Do not discharge into the drains/surface waters/ground water.
Do not discharge into the subsoil/soil.

6.3. Methods and material for containment and cleaning up

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder).

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 4 of 9

Shovel into suitable container for disposal.

6.4. Reference to other sections

Observe protective instructions (see Sections 7 and 8).
Information for disposal see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Ensure adequate ventilation.
Do not breathe vapours.
Avoid contact with skin, eyes and clothing.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.
Take measures against electrostatically charging.
Vapour/air mixture is explosive, even in empty uncleaned receptacles.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep containers tightly closed in a cool, well-ventilated place.

Advice on storage compatibility

Incompatible with oxidizing agents.

Further information on storage conditions

Keep away from food, drink and animal feeding stuffs.

7.3. Specific end use(s)

Lacquer

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
123-86-4	Butyl acetate	150	724		TWA (8 h)	WEL
		200	966		STEL (15 min)	WEL
141-78-6	Ethyl acetate	200	-		TWA (8 h)	WEL
		400	-		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas.

Protective and hygiene measures

Do not inhale vapours.
Wash hands before breaks and immediately after handling the product.
When using do not eat, drink or smoke.
Avoid contact with eyes, skin or oral tissues.
Remove and wash contaminated clothing before re-use.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 5 of 9

Eye/face protection

Tightly fitting goggles (EN 166).
Eye wash bottle with pure water (EN 15154).

Hand protection

Splash protection:
Protective gloves resistant to chemicals made off butyl, minimum coat thickness 0.7 mm, permeation resistance (wear duration) > 30 minutes, i.e. protective glove <Butoject 898> made by www.kcl.de.
This recommendation refers exclusively to the chemical compatibility and the lab test conforming to EN 374 carried out under lab conditions.
Requirements can vary as a function of the use. Therefore it is necessary to adhere additionally to the recommendations given by the manufacturer of protective gloves.

Skin protection

Long sleeved clothing (EN 368).

Respiratory protection

In case of insufficient ventilation wear suitable respiratory equipment (gas filter type A) (EN 14387).

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Various
Odour:	Characteristic

Test method

Changes in the physical state

Initial boiling point and boiling range:	55 °C
Flash point:	- 18 °C
Lower explosion limits:	1,5 vol. %
Upper explosion limits:	13 vol. %
Ignition temperature:	315 °C DIN 51794
Vapour pressure: (at 20 °C)	247 hPa
Density (at 20 °C):	n.d.
Water solubility: (at 20 °C)	Partially miscible
Flow time: (at 23 °C)	20 s DIN 53211/4

9.2. Other information

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No decomposition if stored and applied as directed.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactions with oxidizing agents.

10.4. Conditions to avoid

To avoid thermal decomposition, do not overheat.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 6 of 9

Vapours may form explosive mixture with air.

10.5. Incompatible materials

Strong oxidizing agents

10.6. Hazardous decomposition products

Carbon monoxide (CO), carbon dioxide (CO₂) and nitrogen oxides (NO_x).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

No toxicological data available.

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. ((Ethyl acetate); (n-Butyl acetate))

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Additional information on tests

Classification in compliance with the assessment procedure specified in the Regulation (EC) no 1272/2008.

Practical experience

Other observations

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Inhalation of high vapour concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting.

SECTION 12: Ecological information

12.1. Toxicity

Ecological data are not available.

12.2. Persistence and degradability

No data available.

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

According to Regulation (EC) No 1907/2006 (REACH) none of the substances, contained in this product are a PBT / vPvB substance.

12.6. Other adverse effects

Low hazard to waters.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 7 of 9

Further information

Do not flush into surface water or sanitary sewer system.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Advice on disposal

Can be incinerated, when in compliance with local regulations.
Where possible recycling is preferred to disposal.

Waste disposal number of used product

080111 WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS; wastes from MFSU and removal of paint and varnish; waste paint and varnish containing organic solvents or other hazardous substances
Classified as hazardous waste.

Contaminated packaging

Empty containers should be taken for local recycling, recovery or waste disposal.
Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse.
Packaging that cannot be cleaned should be disposed of like the product.

SECTION 14: Transport information

Land transport (ADR/RID)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2
Transport category: 2
Hazard No: 33
Tunnel restriction code: D/E

Inland waterways transport (ADN)

14.1. UN number: UN 1263
14.2. UN proper shipping name: Paint
14.3. Transport hazard class(es): 3
14.4. Packing group: II
Hazard label: 3



Classification code: F1
Limited quantity: 5 L / 30 kg
Excepted quantity: E2

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 8 of 9

Marine transport (IMDG)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Marine pollutant:	No
Limited quantity:	5 L / 30 kg
Excepted quantity:	E2
EmS:	F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number:	UN 1263
14.2. UN proper shipping name:	Paint
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Limited quantity Passenger:	1 L	
Passenger LQ:	Y341	
Excepted quantity:	E2	
IATA-packing instructions - Passenger:		353
IATA-max. quantity - Passenger:		5 L
IATA-packing instructions - Cargo:		364
IATA-max. quantity - Cargo:		60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

14.6. Special precautions for user

Handle in accordance with good industrial hygiene and safety practice.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

The transport takes place only in approved and appropriate packaging.

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

2004/42/EC (VOC): < 85 %

National regulatory information

Employment restrictions: Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC). Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.

Water contaminating class (D): 1 - slightly water contaminating

Safety Data Sheet

according to Regulation (EC) No 1907/2006

DIE SEALING LACQUER

Revision date: 25.01.2017

Product code: 00310-0024

Page 9 of 9

15.2. Chemical safety assessment

For this substance a chemical safety assessment has not been carried out.

SECTION 16: Other information**Abbreviations and acronyms**

ADR = Accord européen relatif au transport international des marchandises Dangereuses par Route
RID = Règlement concernant le transport international ferroviaire de marchandises dangereuses
ADN = Accord européen relatif au transport international des marchandises dangereuses par voie de navigation intérieure
IMDG = International Maritime Code for Dangerous Goods
IATA/ICAO = International Air Transport Association / International Civil Aviation Organization
MARPOL = International Convention for the Prevention of Pollution from Ships
IBC-Code = International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
REACH = Registration, Evaluation, Authorization and Restriction of Chemicals
CAS = Chemical Abstract Service
EN = European norm
ISO = International Organization for Standardization
DIN = Deutsche Industrie Norm
PBT = Persistent Bioaccumulative and Toxic
vPvB = Very Persistent and very Bio-accumulative
LD = Lethal dose
LC = Lethal concentration
EC = Effect concentration
IC = Median immobilisation concentration or median inhibitory concentration

Relevant H and EUH statements (number and full text)

H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H228	Flammable solid.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

Data of items 4 to 8, as well as 10 to 12, do partly not refer to the use and the regular employing of the product (in this sense consult information on use and on product), but to liberation of major amounts in case of accidents and irregularities.

The information describes exclusively the safety requirements for the product(s) and is based on the present level of our knowledge.

The delivery specifications are contained in the corresponding product sheet.

This data does not constitute a guarantee for the characteristics of the product(s) as defined by the legal warranty regulations.

(n.a. = not applicable; n.d. = not determined)

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)